



porta accessori
built-in accessories holder

battistrada in gomma
rubber wheels

avvolgitubo statico
static hose reel

serbatoio detergente integrato
built-in detergent tank

filtro ingresso acqua ispezionabile
inspectable water intake filter



Caratteristiche Generali

- Carrello a 2 ruote completo di manico ed avvolgitubo (tubo AP 6 m)
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa in alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Protezione termica del motore
- Aspirazione detergente diretta con serbatoio incorporato
- Capacità del serbatoio detergente 1,4 l
- Lunghezza cavo elettrico 5 m

General Features

- Two-wheel trolley with handle and hose reel (6 m HP hose)
- 3 Axial stainless steel pistons wobble-plate pump with aluminium head
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Motor thermal protector
- Built-in detergent tank for direct suction
- Detergent tank capacity 1.4 l
- Electric cable length 5 m



MOD	COD	MAX	MAX							KG NET
		bar	psi	l/h	gph	kW	rpm	Hz	V	kg
391	13692	135	1960	440	116	1,8	3400	1-50-60	220-240	12,6

Accessori standard Standard accessories



Authorized Distributor
KOGO METAL
021-34535091/2
mail@kogo.com.pk
www.kogo.com.pk