



58 Series 5850.5870

IDROPULTRICI ALTA PRESSIONE
high pressure washer

HEAVYPRO



Caratteristiche Generali

- Pompa a pistoni con sistema biella-manovella ad elevate prestazioni
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale in acciaio inox, con sistema di raffreddamento bruciatore a chiocciola azionata da motore elettrico indipendente, doppia serpentina e fondo in cemento refrattario
- Scheda di ritardo per spegnimento caldaia
- Regolazione pressione
- Serbatoio gasolio 8 l, con tappo di scarico
- Termostato
- Aspirazione detergente incorporata
- Filtro acqua e filtro aspirazione gasolio
- Lunghezza cavo elettrico 5 m

General Features

- High performance piston pump with connecting rod system
- Automatic by-pass valve with pump head pressure discharge
- With safety pressure switch to shut down the boiler in case of lack of water
- Stainless steel vertical boiler with coil burner cooling function driven by independent motor, double coil and refractory cement bottom
- Heating boiler shut-down delay circuit
- Pressure adjustment built-in
- Fuel tank with drain plug (8 l)
- Thermostat
- Built-in detergent suction
- Water filter and fuel inlet filter
- Electric cable length 5 m

	5850	5870
	HRC	HRCS
	TSS[®] Total Stop SYSTEM	

MOD	COD									
		bar	psi	l/h	gph	kW	rpm	Hz	V	kg
5850	25672	130	1900	600	159	3	1450	1~50	230	83
5870	25673	150	2200	900	238	3	2800	3~50	400	84

Accessori standard Standard accessories



Authorized Distributor
KOGO METAL
021-34535091/2
mail@kogo.com.pk
www.kogo.com.pk

	°C	°C Max	Δt
	30	150	55
	30	150	70