

HEAVYPRO



Caratteristiche Generali

- Carrello robusto in metallo a due ruote completo di manico
- Pompa a 3 pistoni in ceramica, con sistema biella-manovella
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore elettrico a induzione trifase con protezione termica
- Regolazione della pressione
- Manometro
- Valvola di regolazione flangiata (VRZ)
- Aspirazione detergente incorporata
- Aspirazione detergente regolabile
- Capacità del serbatoio detergente 3 l
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m

General Features

- Heavy-duty two wheeled trolley with handle
- Triplex pump with ceramic pistons and connecting rod system
- Automatic by-pass valve with pressure with pump head pressure discharge
- Three-phase induction motor with thermal protector
- Pressure adjustment
- Pressure gauge
- Flanged pressure unloader (VRZ)
- Built-in detergent suction
- Adjustable detergent injector
- Built-in detergent tank capacity 3 l
- Inspectable water filter
- Electric cable length 5 m



MOD	COD	 MAX		 MAX						 KG NET
		bar	psi	l/h	gph	kW	rpm	Hz	V	kg
1007 †	25150	200	2900	900	238	7,4	1450	50	400 3~	54,8
1007RLW [‡]	25304	200	2900	900	238	7,4	1450	50	400 3~	61,6
1008 [‡]	25305	150	2200	1260	333	7,4	1450	50	400 3~	54,8
1008RLW [‡]	25306	150	2200	1260	333	7,4	1450	50	400 3~	61,6

† A richiesta / On request 230 V · 3~50 Hz 1750 rpm

‡ A richiesta / On request



Accessori standard Standard accessories



1007	1008	
3600400 (low p.)	3600400 (low p.)	Nero/Black
3600480 (00045)	3600680 (00075)	Rosso/Red
3600490 (15045)	3600690 (15075)	Giallo/Yellow
3600500 (25045)	3600700 (25075)	Verde/Green
3600510 (40045)	3600100 (40075)	Bianco/White